



ABIMIG® A 305 LW, ABIMIG® A 355 LW, ABIMIG® A 405 LW

Slijtonderdelen

ABIMIG® A 305 / 355 LW




ABIMIG® A 405 LW




Gasmondstuk

	Ø A	X1		Ø A	X1	
Cilindrisch	Ø 21	71 mm	145.D024	Ø 21	71 mm	145.D024
Conisch	Ø 18	72 mm	145.D021 •	Ø 18	72 mm	145.D021 •
Conisch	Ø 16	69 mm	145.D022	Ø 16	69 mm	145.D022





M8



M8



Contacttip

E-Cu	Ø 0,8	140.0114	140.0114
	Ø 1,0	140.0313	140.0313
	Ø 1,2	140.0442	140.0442
	Ø 1,6	140.0587	140.0587
E-Cu voor Al	Ø 0,8	141.0003	141.0003
	Ø 1,0	141.0008	141.0008
	Ø 1,2	141.0015	141.0015
	Ø 1,6	141.0022	141.0022
CuCrZr	Ø 0,8	140.0117	140.0117
	Ø 1,0	140.0316	140.0316
	Ø 1,2	140.0445 •	140.0445
	Ø 1,6	140.0590	140.0590 •



Contacttiphouder

M8	014.D745 •	014.D745 •
----	------------	------------



Isoleerring

	767.D668 •	015.D080 •
--	------------	------------

Geleider		305 / 355	405	305 / 355	405	305 / 355	405
		3 m	3 m	4 m	4 m	5 m	5 m
Spiraal	0,8	124.0011	-	124.0012	-	124.0015	-
	1,0	124.0026 •	124.D113	124.0031 •	124.D114	124.0035 •	124.D115
	1,2	124.0026 •	124.D113	124.0031 •	124.D114	124.0035 •	124.D115
	1,6	124.0041	124.D116 •	124.0042	124.D117 •	124.0044	124.D118 •
PTFE	0,8	126.0005	-	126.0008	-	126.0011	-
	1,0	126.0021	-	126.0026	-	126.0028	-
	1,2	126.0021	-	126.0026	-	126.0028	-
	1,6	126.0039	-	126.0042	-	126.0045	-
Kool PTFE	0,8	127.0002	-	127.0003	-	127.0004	-
	1,0	127.0005	-	127.0007	-	127.0008	-
	1,2	127.0005	-	127.0007	-	127.0008	-
	1,6	127.0010	-	127.0012	-	127.0013	-

• Standaard uitrusting